

## VEO-XPT24

### 4K HDBASET EXTENDER KIT 10.2 GBPS



#### PRODUCT OVERVIEW

VEO-XPT24 is a professional HDBaseT transmitter/receiver kit for HDMI extension up to 70 meters over category cable. It supports video signal at resolution up to 4K/UHD with embedded multi-channel audio formats like DTS-HD Master Audio and Dolby TrueHD. The extender kit includes bi-directional IR and RS-232 pass-through. VEO-XPT24 is the ideal solution for commercial point-to-point applications that require extension over greater distances than HDMI can support.

#### KEY FEATURES

- Complete extender kit, no configuration needed
- Full HD support: 1080p@60Hz
- 4K/UHD support: up to 4096x2160@30Hz (or 60Hz with YUV 4:2:0)
- 3D support
- Transmission distance up to 70 meters under 1080p and 40 meters under 4K
- Bi-directional IR and RS-232 pass-through
- Use single UTP/STP category cable (CAT-5E/6/7) to substitute HDMI cable to achieve long distance transmission
- POH (RX powered by TX)
- HDCP 2.2/1.4 compliant
- Integrated mounting ears

#### APPLICATIONS

- Retail shops
- Fitness Center
- Sports Bar
- Restaurants
- Hotels
- Residential applications

#### TECHNICAL DATA

##### Audio and Video performances

##### Supported Resolutions

4096x2160@24/25/30/50\*/60Hz\*,  
 3840x2160@24/25/30/50\*/60Hz\*(UHD),  
 2048x1080p,1080p@23.98/24/25/29.97/30/50/59.94/60Hz,  
 1080i@50/59.94/60Hz,  
 720p@50/59.94/60Hz,  
 576p,576i, 480p, 480i

**Vesa**

2560x2048, 2560x1600, 2048x1536,  
 1920x1200, 1680x1050, 1600x1200,  
 1600x900, 1440x900, 1400x1050, 1366x768,  
 1360x768, 1280x1024, 1280x800, 1280x768,  
 1152x864, 1024x768, 800x600, 640x480

\*4096x2160@50/60Hz & 3840x2160@50/60Hz supported @ chroma subsampling 4:2:0 8-bit only

**Colorspace** RGB, YCbCr

**Chroma Subsampling** 4:4:4, 4:2:2, 4:2:0

**Color depth** 8-bit, 10-bit, 12-bit, 16-bit only @1080p

**Signal Bandwidth** 10.2 Gbps

**HDCP** 2.2 Compliant

**CEC** Pass-through

**Audio Formats** PCM 2Ch, LPCM 5.1, LPCM 7.1, Dolby Digital, DTS 5.1, Dolby TrueHD, DTS-HD Master Audio

**Bit rate** up to 24-bit

**Sample Rate** 32 KHz, 44.1 KHz, 48 KHz, 88.2 KHz, 96 KHz, 176.4 KHz, 192 KHz

**HDMI Distance** up to 10 meters (33 ft) with Ecler VEO cables

<b>Distance</b>	CAT.5e/6 @ 4K	up to 35 meters / 115 feet
	CAT.6a/7 @ 4K	up to 40 meters / 130 feet
	CAT.5e/6 @ 1080p	up to 60 meters / 197 feet
	CAT.6a/7 @ 1080p	up to 70 meters / 230 feet

**Operating Temperature** -5 to +35°C (41 to +95 °F)

**Humidity** 5 to 90 % RH (no condensation)

**Power Consumption** 2.5W (TX), 5W (RX) Maximum

**Power Supply** AC 100V ~ 240V 50/60Hz Output: DC 12V---2A

All product characteristics are subject to variation due to production tolerances. NEEC AUDIO BARCELONA S.L. reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications.

Motors, 166-168 08038 Barcelona - Spain - (+34) 932238403 [information@ecler.es](mailto:information@ecler.es) [www.ecler.com](http://www.ecler.com)

MISCELLANEOUS

Dimensions W x H x D 105mm x 25mm x 71mm / 4.13" x 0.98" x 2.79"

Weight 700g / 1,54 lbs (Pair)

MECHANICAL DIAGRAMS

